

MODEL CV

PART 1 – GENERAL

PART 2 – PRODUCTS

(2.01) BULLET RESISTANT CLAMP-ON DRIVE-UP VISION WINDOW: Standard CV, Clamp-on Drive-up Vision Window with UL label by Chicago Bullet Proof Systems, 2595 Bond Street, University Park, IL 60484, tel: (708)-534-9102. *Non-UL labeled assemblies are not acceptable.*

- A. Chicago Bullet Proof Systems Standard CV, Clamp-on Drive-up Vision Window with UL label for assembly. Clamp-on vision window shall be constructed from Chicago Bullet Proof's certified Shot-Tex bullet-resistant steel and shall bear a UL label. Clamp-on vision window shall be complete with adjustable frame for wall thickness from 8 inches to 11 inches; with applied glazing stop on the protected side. Transparent armor shall be retained within a subframe which is inclined five degrees to vertical, slanted away from the protected side of the window. Frame shall be four sided with mitered and fully welded corners. Exposed welds shall be ground smooth and finished flush with adjoining surfaces, free of holes or defects.
- B. Clamp-on vision window shall be Model CV with overall size of _____ inches wide by _____ inches high.
- C. Frame Finish: Finish for clamp-on vision window frame shall be _____. (prime painted or stainless steel with brushed finish).
- A. Glass Armor: UL 752 listed bullet resistant transparent armor (Laminated Glass or Glass Clad Polycarbonate) of _____(see below) thickness and UL listed level _____(see below).

<u>Laminated Glass Thickness</u>	<u>Glass Clad Polycarbonate Thickness</u>	<u>UL level*</u>
1-1/4"	3/4"	Level 1
	15/16"	Level 2
1-3/4"	1-1/8"	Level 3
	1-3/16"	Level 4

- B. Clamp-on vision window assembly shall be UL listed and labeled to ballistic levels defined in the Standard for Safety UL 752 for level* _____. (select one: level 1, level 2, level 3, level 4, or level 6).

***Consult CBP's list of UL label definitions to select the best level for your application.**

- Notes:**
- 1. The CV120 and CV180 have one vertical division mullion dividing the frames into two equal panels.
 - 2. Special frame, glass, and size conditions are available, contact manufacturer.

PART 3 – EXECUTION