

MODEL GP3

PART 1 - GENERAL

PART 2 - PRODUCTS

(2.01) GUNPORT: Standard GP3 Gunport with UL label by Chicago Bullet Proof Systems, 12 E. Old Mill Lane, Burr Ridge, IL 60527, tel: 800.690.9160, fax: 312.492.7406. *Non-UL labeled assemblies are not acceptable.*

- A. Chicago Bullet Proof Systems Standard GP3 Gunport with UL label for assembly shall be constructed from UL listed Shot-Tex bullet-resisting steel and shall bear a UL label. gunport shall be the following type(s):
 - 1. Wall Mount Type GP3: Complete with Cover of Shot-Tex #1-S, stainless steel with satin finish; and a self-locking sliding cover plate of Shot-Tex #4A1 steel with brushed stainless steel finish. The Mounting Plate of Shot-Tex #3 steel for level 3 (or Shot-Tex #4A1 steel for level 4) shall be prime painted flat black.
 - 2. Glass Mount Type GP3: Complete with a Cover of Shot-Tex #1-S, stainless steel with satin finish, and a self-locking sliding cover plate of Shot-Tex #4A1 steel with brushed stainless steel finish. Mounting Ring shall be stainless steel with a satin finish. Gunport shall require a 6 inch diameter hole in glass.
- B. Weapon opening shall be 3 inches in diameter.
- C. Trigger plate shall completely cover firing port when not in use. Trigger plate shall be tamper resistant from the threat side and shall open on the non-threat side by sliding vertically. Trigger plate shall be spring-loaded for closing.
- D. Gunport shall be UL listed and labeled to ballistic level defined in the Standard for Safety UL 752 for level* _____(select one: level 3, level 4, level 5, or level 8).

** Consult CBP's list of UL label definitions to select the best level for your application.*

PART 3 - EXECUTION