

## MODEL GP4

### PART 1 - GENERAL

### PART 2 - PRODUCTS

(2.01) GUNPORT: Standard GP4 Gunport with UL label by Chicago Bullet Proof Systems, 12 E. Old Mill Lane, Burr Ridge, IL 60527, tel: 800.690.9160, fax: 312.492.7406. *Non-UL labeled assemblies are not acceptable.*

- A. Chicago Bullet Proof Systems Standard GP4 Gunport with UL label for assembly shall be constructed from UL listed Shot-Tex bullet-resisting steel and shall bear a UL label. Gunport shall be the following type(s):
  - 1. Wall Mount Type GP4: Complete with Cover of Shot-Tex #1-S, stainless steel with satin finish; Slide and Mounting Plate of Shot-Tex #4A1 shall be prime painted flat black.
- B. Weapon opening shall be 8 inches wide (or 12 inches) by 4 inches high.
- C. Trigger plate shall completely cover firing port when not in use. Trigger plate shall be tamper resistant from the threat side and shall open on the non-threat side by sliding vertically. Trigger plate shall be spring-loaded for closing and shall be self-latching when closed.
- D.. Gunport shall be UL listed and labeled to ballistic level defined in the Standard for Safety UL 752 for level\* level 4.

*\* Consult CBP's list of UL label definitions to select the best level for your application.*

### PART 3 - EXECUTION